



DECLARATION OF PERFORMANCE

DOP TIW 0501

1. Unique identification code of the product-type:

parquet - EN 13489 9,5 - 25mm 600 kg/m³

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Timberman

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Timberman Denmark A/S, Havnevej 11, 9560 Hadsund

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).

EPH -Dresden - Germany, CWFT

not applicable




Notified Body

certificate of constancy of performance

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire		EN 14342: 2005+A1 2008
Content of Pentachlorophenol		EN 14342: 2005+A1 2008
Formaldehyd Emissions		EN 14342: 2005+A1 2008
Slip resistance	NPD	EN 14342: 2005+A1 2008
biological durability	class 1	EN 14342: 2005+A1 2008
breaking strength	2,5 kN (600-610 mm)	EN 14342: 2005+A1 2008
Thermal conductivity [W/mK]	Th res (m ² K/W) = 0,106 (12,5)- 0,20 (25)	EN 14342: 2005+A1 2008
Water-tightness		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Bjarne Pedersen, indkøbschef

(name and function)

Hadsund 28. Juni, 2013

(place and date of issue)

Bjarne Pedersen

(signature)